



# VersaPro™ 80% AFUE GAS FURNACE MGA80EE\*\*\*\*B



- ✓ Quiet Operation
- ✓ Superior Performance
- ✓ Durable Build & Finish
- ✓ Optional LP Kit
- ✓ Multi-Position Application
- ✓ 80% AFUE
- ✓ Two Stage
- ✓ Energy Efficient
- ✓ Compact Design

48 Remington Way  
Hickory, KY 42051  
270.366.0457

[www.mrcool.com](http://www.mrcool.com)

Version Date: 07-30-2024



# VersaPro™ 80% AFUE GAS FURNACE†

**MGA80EE\*\*\*\*\*B**

In the face of even the harshest winter conditions, the MRCOOL® VersaPro™ 80% AFUE Gas Furnace guarantees reliable and high quality warmth and comfort within your home. Its sturdy construction and space-efficient design cater to various cabinet sizes, facilitating easy installation, replacement, and maintenance, even in areas where space is limited.

The furnace's two-stage consistent flow DC motor ensures energy efficiency and cost savings, while the hot-surface ignition ensures dependable operation you can count on.

The multi-speed direct-drive blower operates quietly, seamlessly integrating with your daily activities without disruption. Its AHRI certification and ETL listing guarantee the unit has undergone rigorous testing to meet the highest quality and performance standards.

Registering the furnace within 90 days of installation activates a 10-year parts warranty and lifetime heat exchanger warranty, providing peace of mind. Even without registration, your unit is protected by a 5-year parts warranty and 20-year heat exchanger warranty, promising long-term reliability and comfort.

## SPECIFICATION

## GAS FURNACE - 80% AFUE

MODEL NO	Unit	MGA80EE040A3B	MGA80EE060B4B	MGA80EE080B4B	MGA80EE080C4B	MGA80EE100C5B	MGA80EE120D5B	
Power Supply	V~Hz, Ph	115~60, 1	115~60, 1	115~60, 1	115~60, 1	115~60, 1	115~60, 1	
Nat. Gas/LP	Input	Btu/h	40,000	60,000	80,000	80,000	100,000	120,000
	Output	Btu/h	32,000	48,000	64,000	64,000	80,000	96,000
Blower Size	inch	11.18 x 6.14	11.18 x 9.64	11.18 x 9.64	11.18 x 11.18	11.18 x 11.18	12.75 x 11.25	
Temp. Rise Range	°F	20-50	25-55	30-60	30-60	30-60	35-65	
Cabinet Size (WxDxH)	inch	14.49 x 28.5 x 33.74	17.5 x 28.5 x 33.74	17.5 x 28.5 x 33.74	20.98 x 28.5 x 33.74	20.98 x 28.5 x 33.74	24.49 x 28.5 x 33.74	
Packing Size (WxDxH)	inch	16.77 x 31.02 x 40	19.76 x 31.02 x 40	19.76 x 31.02 x 40	23.27 x 31.02 x 40	23.27 x 31.02 x 40	26.77 x 31.02 x 40	
Motor	HP	1/2	1/2	1/2	1/2	1	1	
Max Airflow Rate (0.5ESP)	CFM	1200	1600	1600	1600	2000	2000	
Motor Speeds		5 speed	5 speed	5 speed	5 speed	5 speed	5 speed	
Gas Type		NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)	
Gas Connection Size	inch	3/4	3/4	3/4	3/4	3/4	3/4	
Net Weight	lbs	108	115	128	135	146	152	
Gross Weight	lbs	132	141	155	163	177	190	



Data provided by AHRI



†Registered Warranty provides for a total of 10 years of limited warranty coverage (Standard 5-year limited parts warranty plus an additional 5-year limited extended parts warranty; Lifetime heat exchanger warranty when registered). Warranty must be registered online within 60 days of installation to qualify for extended coverage. Unregistered equipment defaults to 5-year coverage.