



# VersaPro™ Series 13.4 SEER2 PACKAGED GAS/ELECTRIC



When the weather outside is unpredictable, your home should remain an oasis of comfort.

- ✓ Included LP Conversion Kit
- ✓ Quiet Multi-Speed Blower
- ✓ Durable Build & Finish
- ✓ Direct Spark Ignition
- ✓ High Quality Heat Exchanger
- ✓ Multi-Position Installation
- ✓ 81% AFUE
- ✓ Convenient Access Panels

48 Remington Way  
Hickory, KY 42051  
270.366.0457

[www.mrcool.com](http://www.mrcool.com)

Version Date: 07-30-2024



# VersaPro™ Series 13.4 SEER2 Packaged Gas/Electric

**MPG\*\*S\*\*\*M413B**

By integrating a high-performance 13.4 SEER2 air conditioner with a robust 81% AFUE gas furnace, this efficient package unit not only ensures optimal comfort but also delivers substantial savings on your utility bills. What sets this unit apart is its versatility, offering customizable options such as horizontal or downflow applications and the capability to convert to propane with an optional LP kit.

\*Data provided by AHRI



† If registered online within 90 days, warranty provides for a total of 10 years of limited parts warranty coverage, plus a 10 year compressor warranty. Warranty must be registered online within 90 days of installation to qualify for extended coverage. Unregistered equipment defaults to 5-year parts and compressor warranty.

## SPECIFICATION

## VERSAPRO™ PACKAGE GAS ELECTRIC

MODEL NO.	Unit	MPG24S060M413B	MPG30S060M413B	MPG36S090M413B	MPG42S090M413B	MPG48S090M413B	MPG60S110M413B
Power Supply	V~Hz, Ph	208/230 ~ 60, 1	208/230 ~ 60, 1	208/230 ~ 60, 1	208/230 ~ 60, 1	208/230 ~ 60, 1	208/230 ~ 60, 1
Cooling Capacity	Btu/h	24000	30000	36000	42000	48000	60000
SEER2	Btu/W	13.4	13.4	13.4	13.4	13.4	13.4
Heating Input	Btu/h	60000	60000	90000	90000	90000	110000
Output	Btu/h	48000	48000	72000	72000	72000	88000
Temp. Rise Range	°F	30-60	30-60	40-70	36-65	30-60	30-60
AFUE	%	81	81	81	81	81	81

### Electrical Data

Min/Max Voltage	V	187/253	187/253	187/253	187/253	187/253	187/253
Max Current Ampacity (MCA)	A	19	21	23	28	31	37
Max Current Over Protection (MOP)	A	25	30	35	40	50	60

### Fan Motor

Outdoor	Horsepower	HP	1/12	1/6	1/6	1/3	1/3	1/3
	Full Load Amps (FLA)	A	0.61	1	1	1.9	1.9	1.9
	Rated RPM	RPM	900	850	850	1050	1050	1050
Indoor	Horsepower	HP	1/2	1/2	1/2	3/4	3/4	3/4
	Full Load Amps (FLA)	A	4.2	4.2	4.2	5.7	5.7	5.7
	Rated RPM	RPM	1050	1050	1050	1050	1050	1050

### Dimensions

Net (WxDxH)	inch	35.08 x 50.67 x 46.85	35.08 x 50.67 x 46.85	35.08 x 50.67 x 46.85	35.08 x 50.67 x 46.85	44.88 x 51.57 x 51.42	44.88 x 51.57 x 51.42
Packing (WxDxH)	inch	36.81 x 52.36 x 48.78	36.81 x 52.36 x 48.78	36.81 x 52.36 x 48.78	36.81 x 52.36 x 48.78	45.43 x 52.32 x 52.36	45.43 x 52.32 x 52.36
	Net Weight	lbs	428	437	443	474	560
	Gross Weight	lbs	443	450	456	489	582
Refrigerant Type	Type	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A
Refrigerant Charge	oz	47.6	52.9	52.9	70.5	72.3	74.1
Sound Rating	dB(A)	79	79	79	80	80	80